



# GWR-HS HIGH SPEED

CELLULAR ROUTER SERIES

HSPA • HSPA+ • LTE



GWRHS cellular router series represents a group of high speed routers specially designed for those applications where high speed data transfers (up to 100 Mbps) over GSM network are required. Complete series is based on reliable and high performance hardware platform including ARM Cortex-A8 microprocessor.

GWRHS series inherited the basic concept of GWR cellular router series – RELIABILITY COMES FIRST. Therefore all router models have dual SIM card support. This router series also supports additional WiFi option.

Many useful features make GWRHS cellular routers a perfect solution for wide variety of mobile broadband applications (video surveillance, digital signage, mobile office and retail/point-of-sale, field service ...):

- Dual SIM card support increases the reliability of the router and provides a solution for those applications where failure of one mobile network must not result in system downtime. Automatic failover feature will detect the failure of primary connection and automatically switch to alternative connection. When the connectivity over primary connection is restored GWR router will perform switchover to primary connection.
- The whole set of advanced WAN settings allow a user to specify desired parameters in order to meet the requirements of specific cellular network. GWR routers proved themselves to be reliable and high performance devices in so many countries around the world. All advanced parameters included represent the result of detailed analysis of large number of different cellular networks. In few simple steps it is possible to optimize the performance of the router on almost any cellular network.
- VPN (GRE, IPsec and OpenVPN) tunnel support provides powerful options for network expansion and secure data transfer over the cellular network.
- With Serial-to-IP feature it is possible to connect, control and perform data acquisition from almost any device with serial RS232 port. In addition to this feature, GWR router series implements ModbusRTU-to-ModbusTCP functionality designed to support expansion of Modbus SCADA networks over the cellular networks.
- Easy to use web interface, extended CLI (Command Line Interface), detailed log, SMS control feature, partial and full configuration Export/Import and remote management and monitoring software provide wide range of management functionalities. All those features and tools empower a user with full control over GWR routers.

## Technical specifications

### RF characteristics

#### GPRS/EDGE/UMTS/HSPA

UMTS/HSDPA/HSUPA Quad band: 850/900/1900/2100 MHz  
GSM/GPRS/EDGE Quad band: 850/900/1800/1900 MHz  
GPRS/EDGE multi-slot class 12, mobile station class B  
HSDPA DL: 7.2Mbps, HSUPA UL: 5.76Mbps  
UMTS DL: 384Kbps, UL: 384Kbps  
EDGE DL: 236.8Kbps, UL: 236.8Kbps  
GPRS DL: 85.6Kbps, UL: 85.6Kbps

#### GPRS/EDGE/UMTS/HSPA/HSPA+

UMTS/ HSDPA/HSUPA/HSPA+: Quad band: 850/900/1900/2100 MHz  
GSM/GPRS/EDGE Quad band: 850/900/1800/1900 MHz  
GPRS/EDGE multi-slot class 12, mobile station class B  
HSPA+ DL: 21Mbps, UL: 5.76Mbps  
HSDPA DL: 7.2Mbps, HSUPA UL: 5.76Mbps  
UMTS DL: 384Kbps, UL: 384Kbps  
EDGE DL: 236.8Kbps, UL: 236.8Kbps  
GPRS DL: 85.6Kbps, UL: 85.6Kbps

#### GPRS/EDGE/UMTS/HSPA/HSPA+/LTE

LTE Five band: 800/900/1800/2100/2600 MHz  
UMTS/ HSDPA/HSUPA/HSPA+ Dual band: 900/2100 MHz  
GSM/GPRS/EDGE Three band: 900/1800/1900 MHz  
GPRS multi-slot class 10, mobile station class B  
EDGE multi-slot class 12, mobile station class B  
LTE DL: 100Mbps, UL: 50Mbps  
HSPA+ DL: 21Mbps, UL: 5.76Mbps  
HSDPA DL: 14.4Mbps, HSUPA UL: 5.76Mbps  
UMTS DL: 384Kbps, UL: 384Kbps  
EDGE DL: 236.8Kbps, UL: 236.8Kbps  
GPRS DL: 85.6Kbps, UL: 85.6Kbps

#### Wi-Fi

- Wireless Standards
  - IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
- Frequency Band
  - 2.4GHz to 2.472GHz(1 to 13 channels)
- Rates
  - 11b: 1, 2, 5.5, 11Mbps
  - 11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps
  - 11n: 6.5, 7.2, 13, 14.4, 19.5, 21.7, 26, 28.9, 39, 43.3, 52, 57.8, 58.5, 65, 72.2Mbps
- Minimum Reception Sensitivity
  - 802.11b: -87dBm; 802.11g: -73dBm; 802.11n: -68dBm
- Transmit output power
  - 802.11b: 17dBm; 802.11g: 15dBm; 802.11n: 14.5dBm
- Wireless Security
  - WEP 64 and 128 bits, WPA-PSK, WPA2-PSK, WPA-PSK/WPA2-PSK

### Interfaces and connectors

- 1x embedded interface HSPA/HSPA+/LTE (depending on the router model)
- Dual SIM slots
- GSM: 2xSMA female connectors (50 Ω) for external antenna
- WiFi: RPSMA male connector (50 Ω) for external antenna
- 1x Ethernet interface 10/100 Base-T (LAN)
- 1x Serial RS-232 interface
- 1x USB Host 2.0 interface

### Status LED

- Ethernet activity/network traffic • Power on • GSM link activity
- WiFi link activity • Signal quality • Reset

### Power requirements

12VDC / 1A

### Environmental

- Operating temperature: -10° C to 55° C (14° F to 131° F)
- Storage temperature: -20° C to +85° C (-4° F to +185° F)
- Relative humidity: 5% to 95% (non-condensing)

### Housing

- Robust metal housing with optional DIN rail mounting kit

### Dimensions and weight

- Size (W x D x H): 95 x 135 x 35 mm
- Weight: 380 gr

### Management

- Web application (HTTP based); Command Line Interface on serial console, telnet and SSH; GWR connection wizard; Remote management and monitoring software; Detailed system log; Default reset; Firmware upload; Partial or full configuration Export/Import

## Protocols and features

### Network


- DHCP server • RIP • Port forwarding • DMZ support
- SNMPv1,2c • DynDNS • NTP • Firewall (NAT, PAT, IP filtering)
- Serial-to-IP • ModbusRTU-to-ModbusTCP

### VPN

- GRE
- GRE Keepalive
- IPsec pass-through
- IPsec
  - Data integrity
    - HMAC-MD5, SHA-1
    - Authentication and key management
- IKE, manual keys
- IKE features
  - Perfect Forward Secrecy
  - Auth-Method PSK
  - Identify IP address
  - DPD for constant connection
  - Automatic NAT-T behind NAT
  - Initiator and responder
- IPSec tunnel failover
- OpenVPN

### Ordering information

Part Number	Router description
GWRHS352	High-Speed Cellular GPRS/EDGE/UMTS/HSPA
GWRHS352-WIFI	High-Speed Cellular GPRS/EDGE/UMTS/HSPA with 802.11bgn Wi-Fi
GWRHS352P	High-Speed Cellular GPRS/EDGE/UMTS/HSPA/HSPA+
GWRHS352P-WIFI	High-Speed Cellular GPRS/EDGE/UMTS/HSPA/HSPA+ with 802.11bgn Wi-Fi
GWRHS402	High-Speed Cellular GPRS/EDGE/UMTS/HSPA/HSPA+/LTE
GWRHS402-WIFI	High-Speed Cellular GPRS/EDGE/UMTS/HSPA/HSPA+/LTE with 802.11bgn Wi-Fi



## CONTACT US

**Geneko Sales Team**  
e-mail: gwrsales@geneko.rs

**Geneko Support Team**  
e-mail: gwrsupport@geneko.rs

Bul. Despota Stefana 59a  
11000 Belgrade • Serbia

Phone: +381 11 3340-591, 3340-178  
Fax: +381 11 3224-437  
www.geneko.rs