

RBMTX-Hx2

Anywhere you go



The RBMTX-Hx2 is a small modem made for wireless m2m applications. It is a compact device with all the standard interfaces and Dual SIM option powered by Telit HE910 embedded engine. Supporting GPRS/EDGE/UMTS/HSPA+ it is dedicated for users seeking for easy and fast mobile Internet access. Internet connection is easily available and configurable via internet browser without any need of installing software or drivers for the device.

RBMTX-Hx2 is a universal solution for all low-volume M2M and mobile data applications including metering, traffic systems, transportation and logistics, security, vending machines and facility management.

- GSM/GPRS/EDGE/UMTS/HSPA+
- LAN
- Compact size
- Plug & Play
- RS232/485
- External RF
- DUAL SIM

TELEORIGIN

ul. Szymanowskiego 13, 05-092 Łomianki
tel. + 48 22 751 76 80, fax. + 48 22 751 76 81
info@teleorigin.com

RBMTX-Hx2

Anywhere you go



| Hardware | Standard | Possible Upgrade |
|--------------------|---|-------------------------------------|
| Power supply | 6-30 V | — |
| CPU | ARM9 450 MHz | — |
| Internal Memory | 128 MB RAM | 256 MB RAM, 512 MB RAM |
| RS iniface | RS232 or RS485 via RJ45 connector | — |
| LAN | Ethernet 100 Mbps | — |
| Network connection | HSPA+ 21 / 5.76 Mbps | — |
| WiFi | — | 802.11 b/g |
| Dual SIM | 2 x external SIM holders | 2 x internal SIM holders, e-SIMs |
| GPS | — | GPS or GPS/GNSS |
| Antenna | SMA connector | — |
| Software | | |
| Management: | DCHP (client/server), IEEE 802.1Q tagging, IPsec, OpenVPN, Firewall, NAT, PAT, DDNS, CARP, Static routing, Access Control, Syslog | |
| Advanced: | RS-232/485-TCP/UDP forwarding, ModBus gateway, NTRIP, SMS server. NTP | |



TELEORIGIN

ul. Szymanowskiego 13, 05-092 Łomianki
tel. + 48 22 751 76 80, fax. + 48 22 751 76 81
info@teleorigin.com